





Visual	Brief Description	Specifications: Dimensions: External / Internal (H x W x L) Weight	Payload Volume	Temperature Ranges
	<ul style="list-style-type: none"> ▪ Under proprietary construction, launching soon. ▪ Electric, plug-in reefer ▪ Dual climate control compartments ▪ Multiple operating modes 	<p>External:</p> <ul style="list-style-type: none"> ▪ 180.7in x 70.7in x 79.3in <p>Internal:</p> <ul style="list-style-type: none"> ▪ 72.6 in x 59.8 in x 59.1 in 	<p>3,831 L (130 ft³)</p>	<ul style="list-style-type: none"> ▪ Below 0° ▪ 2°C to 8°C (36°F to 46°F) ▪ 15°C to 25°C (59°F to 77°F)
	<ul style="list-style-type: none"> ▪ Proprietary construction, Fiberglass body, polyurethane insulation ▪ Back-up battery system ▪ Double barn door construction allows for loading of standard pallets directly into container ▪ Can be moved using forklift and loaded into back of larger trucks 	<p>External :</p> <ul style="list-style-type: none"> ▪ 66 in x 50 in x 58 in <p>Internal:</p> <ul style="list-style-type: none"> ▪ 60 in x 44 in x 52 in 	<p>2264 L (80 ft³)</p>	<ul style="list-style-type: none"> ▪ Below 0° ▪ 2°C to 8°C (36°F to 46°F) ▪ 15°C to 25°C (59°F to 77°F)
	<ul style="list-style-type: none"> ▪ Rugged design withstands the abuse of transportation ▪ Operates globally via any power source ▪ Multiple operating modes ▪ Refrigerator mode ▪ Freezer mode ▪ Heater mode for low ambient temps ▪ Assured payload integrity 	<p>External :</p> <ul style="list-style-type: none"> ▪ 21.8 in x 21 in x 37.5 in <p>Internal:</p> <ul style="list-style-type: none"> ▪ 13 in x 14 in x 18 in) <p>Empty Weight:</p> <ul style="list-style-type: none"> ▪ 64.5 kgs (142 lb) 	<p>56.6 L (2 ft³)</p>	<p>Operating:</p> <ul style="list-style-type: none"> ▪ -20°C to 49°C (-4°F to 120°F) <p>Storage:</p> <ul style="list-style-type: none"> ▪ -30°C to 65°C (-22°F to 149°F)
	<ul style="list-style-type: none"> ▪ Rugged design withstands abuse ▪ Ensure payload integrity ▪ Extended hold times without ice and with no active cooling ▪ Multiple storage temps with versatile and reliable PXC Coolant Packs 	<p>Internal Payload:</p> <ul style="list-style-type: none"> ▪ 2.0 in x 3.3 in x 9.3 in <p>Weight:</p> <ul style="list-style-type: none"> ▪ 2.1 kg (4.6 lb) <p>PCM Packs:</p> <ul style="list-style-type: none"> ▪ Each PXC Coolant Pack measures 9 in x 3.87 in ▪ x 1 in 	<p>1.0 L (61 in³)</p>	<ul style="list-style-type: none"> ▪ 2°C to 8°C (36°F to 46°F) ▪ -10°C below ▪ -15°C below ▪ -20°C below ▪ Approximate hold time up to 20 hours

